



P.C.B LAYOUT TOP VIEW

NOTES

MATERIAL

- 1. HOUSING MATERIAL : GLASS FILLED POLYESTER UL94V-0.
- 2. CONTACT MATERIAL : PHOSPHOR BRONZE T=0.35mm.
- 3. PLATING : CONTACT AREA-SELECTIVE GOLD PLATING, TAILS PLATING TIN OVER NICKEL. : 3U", 6U", 15U", 30", 50".

ELECTRICAL

- 1. VOLTAGE RATING : 125 VAC RMS.
- 2. CURRENT RATING : 1.5 AMP.
- 3. CONTACT RESISTANCE : 30 MILLIOHMS MAX.
- 4. INSULATION RESISTANCE : 500 MEGOHMS MIN @ 500V DC .
- 5. DIELECTRIC DIELECTRIC RESISTANCE : 1000V AC RMS 50Hz. 1MIN.
- 6. UL Certification : File Number E484635.

MECHANICAL

- 1. DURRABILITY : 750 CYCLES MIN.
- 2. PCB RETENTIONPRE-SOLDER : 1 LB MIN.

ENVIRONMENTAL:

- 1. STORAGE : -40°C ~ +85°C.
- 2. OPERATION : -40°C ~ +85°C.



TOLERANCES 公差		DATE 日期	2017-07-18		LINK-PP INT'L TECHNOLOGY CO., LIMITED			
mm	.0± 0.30 ±	MATERIAL 材质			TITEL 品名		Vertical RJ45 1*1 Connector (10P 10C)	
	.00± 0.25 ±	FINISH 电镀			PART NO. 料号		LPJE620DNL	
	.000± 0.10 ±	SCALE 比	1:1	UNIT 单位	mm	SIZE A4		
ANGLES	± 1°	THIRD ANGLE PROJECTION	Designed 例设计	TOM	Checked 审核	10	Approved 核准	SHEET 1 OF 1